

## **CITY OF TOLLESON GENERAL NOTES FOR UTILITY CONSTRUCTION**

1. All utility construction shall conform to the latest Maricopa Association of Governments (MAG) Uniform Standard Specifications and Details for Public Works Construction.
2. All work performed in the City of Tolleson rights-of-way shall be governed by the latest editions of the Manual on Uniform Traffic Control Devices and the City of Phoenix Traffic Barricade Manual.
3. This set of plans was reviewed by the City of Tolleson City Engineer in compliance with City requirements. However, such review shall not prevent the City from requiring correction of errors found to be in violation of any law, ordinance or City of Tolleson requirement for utility construction in City rights-of-way.
4. The contractor shall have a copy of the approved/stamped construction plans and approved traffic control plan at the project site at all times.
5. All utilities crossings paved streets or alleys must be bored unless permission to open cut has been approved in writing by the City Engineer.
6. Trench backfill within unpaved alleys shall be aggregate base course material conforming to Sections 601 and 702 of MAG Specifications.
7. Pavement replacement within paved streets, if allowed, shall be per MAG Standard Detail No. 200 T Top with full depth CLSM backfill. Pavement mix design must be approved by the City Engineer. Sawcut lines shall be crack sealed with a rubberized crack sealer after pavement has been replaced and cured - use Crafco PolyFlex Type 2 or approved equal.
8. The utility company shall contact the City of Tolleson Building Department (623/936-7111) a minimum of 48 hours prior to the start of work to schedule inspections.
9. The contractor shall notify the City of Tolleson Public Works Department (623/936-3381) a minimum of 48 hours prior to the start of work in any alleys in order to coordinate refuse collection.